



Gli innesti meccanici con due frecce direzionali sono: REVERSIBILI  
Les embrayages mécaniques avec deux flèches de direction sont: REVERSIBLES  
The mechanical couplings with two direction arrows are REVERSIBLE  
Mechanische Kupplungen mit zwei Richtungsfeilen sind in der Drehrichtung UMKEHRBAR.

Coppia Nominale Couple nominal Nominal torque Nenn Drehmoment	Velocità max. Vitesse maxi. Max. speed Max. Drehgeschwindigkeit	Potenza max. trasmissibile Puissance maxi transmissible Max. power output Max. übertragbare Leistung	Carico assiale Charge axial Axial load Längsbelastung
<b>58 daNm</b>	<b>2700 RPM</b>	<b>Kw 60</b>	<b>260 daNm</b>

CODICE CODE CODE No. CODENUMMER	SENSO DI ROTAZIONE SENS ROTATION DIRECTIO OF ROTATION DREHRICHTUNGB
<b>30500</b>	REVERSIBILE - REVERSIBLES - REVERSIBLE - REVERSIBEL
<b>30501</b>	DESTRO - DROITE - RIGHT - RECHTSLAUFIG
<b>30502</b>	SINISTRO - GAUCHE - LEFT - LINKSLAUFIG

CODICE CODE CODE No. CODENUMMER	FLANGIA: TIPO BRIDE: TYPE FLANGE: TYPE FLANSCHTYPE	A	B	C	D	EH 7	FG	H	I	L	M	N
<b>30400</b>	Gr.2							17	21			
<b>30401</b>	Gr.3							21	23			
<b>30402</b>	Gr. 3.5	49.3	149.5	114.3	M10x20	60.3		11.5	24			
<b>30403</b>	Gr. 4	64.5	188	143	M12x22	63.5		16	23			
<b>30417</b>	Gr. 3 BOSCH	48	145	102	M10x15	105		12	19			
<b>30420</b>	SAE A					82.55	M12x20	21	25	106		M12x25
<b>30422</b>	SAE B					101.6	M12x20	12	25	146		M12x25 127
<b>30432</b>	SAE C					127	M14x25	16	28	181		M16x25 162
<b>30461</b>	L.G. 20-35				M10x16	100		25	34		160	
<b>30462</b>	L.G. 50				M10x25	100		32.5	41		160	
<b>30463</b>	L.G. 75				M12x25	105		33	41		180	
<b>30471</b>	ULTRA 3PL DOWTY	52.5	53.4	105.1	M10x20	101.6		10.5	24.5			